






Green Pin® Bow Shackle BN

Standard bow shackle with safety bolt



G-4163



- **Material:** bow and pin high tensile steel, grade 6, quenched and tempered
- **Safety Factor:** MBL equals 6 x WLL
- **Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 3, grade A, from 2 t and upward these shackles comply with ASME B30.26
- **Finish:** hot dipped galvanized
- **Temperature Range:** -40°C up to +200°C
- **Certification:** 2.1 2.2 3.1 MTC³ DNV GL 2.7-1³ * DNV GL 2.7-1³ * DNV GL 0378 CE ABS PDA ABS MA

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	kg
0.5	7	8	16.5	7	12	29	20	48.5	42	34	4	0.06
0.75	9	10	20	9	13.5	32	22	56	50	40	5	0.11
1	10	11	22.5	10	17	36.5	26	63.5	60	46	8	0.16
1.5	11	13	26.5	11	19	43	29	74	67	51	11	0.22
2	13.5	16	34	13	22	51	32	89	82	58	13	0.42
3.25	16	19	40	16	27	64	43	110	98	75	17	0.74
4.75	19	22	46	19	31	76	51	129	114	89	19	1.18
6.5	22	25	52	22	36	83	58	144	130	102	22	1.77
8.5	25	28	59	25	43	95	68	164	150	118	25	2.58
9.5	28	32	66	28	47	108	75	185	166	131	27	3.66
12	32	35	72	32	51	115	83	201	178	147	30	4.91
13.5	35	38	80	35	57	133	92	227	197	162	33	6.54
17	38	42	88	38	60	146	99	249	202	175	39	8.19
25	45	50	103	45	74	178	126	300	249	216	51	14.22
35	50	57	111	50	83	197	138	331	269	238	63	19.53
42.5	57	65	130	57	95	222	160	377	301	274	75	28.33
55	65	70	145	65	105	260	180	433	330	310	90	39.59
85	75	83	162	73	127	329	190	527	380	340	110	62

In inch

working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	weight each
t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	j inch	k inch	lbs
0.5	¹ / ₄	⁵ / ₁₆	²¹ / ₃₂	⁹ / ₃₂	¹⁵ / ₃₂	¹ ⁵ / ₃₂	²⁵ / ₃₂	¹ ²⁹ / ₃₂	¹ ²¹ / ₃₂	¹ ¹¹ / ₃₂	⁵ / ₃₂	0.13
0.75	⁵ / ₁₆	³ / ₈	²⁵ / ₃₂	¹¹ / ₃₂	¹⁷ / ₃₂	¹ ¹ / ₄	⁷ / ₈	² ⁷ / ₃₂	¹ ³¹ / ₃₂	¹ ⁹ / ₁₆	³ / ₁₆	0.25
1	³ / ₈	⁷ / ₁₆	⁷ / ₈	¹³ / ₃₂	²¹ / ₃₂	¹ ⁷ / ₁₆	¹ ¹ / ₃₂	² ¹ / ₂	² ³ / ₈	¹ ¹³ / ₁₆	⁵ / ₁₆	0.34
1.5	⁷ / ₁₆	¹ / ₂	¹ ¹ / ₃₂	⁷ / ₁₆	³ / ₄	¹ ¹¹ / ₁₆	¹ ⁵ / ₃₂	² ²⁹ / ₃₂	² ⁵ / ₈	²	⁷ / ₁₆	0.48
2	¹ / ₂	⁵ / ₈	¹ ¹¹ / ₃₂	¹ / ₂	⁷ / ₈	²	¹ ¹ / ₄	³ ¹ / ₂	³ ⁷ / ₃₂	² ⁹ / ₃₂	¹ / ₂	0.92
3.25	⁵ / ₈	³ / ₄	¹ ⁹ / ₁₆	⁵ / ₈	¹ ¹ / ₁₆	² ¹⁷ / ₃₂	¹ ¹¹ / ₁₆	⁴ ¹ / ₃₂	³ ²⁷ / ₃₂	² ¹⁵ / ₁₆	²¹ / ₃₂	1.62
4.75	³ / ₄	⁷ / ₈	¹ ¹³ / ₁₆	³ / ₄	¹ ⁷ / ₃₂	³	²	⁵ ³ / ₃₂	⁴ ¹ / ₂	³ ¹ / ₂	³ / ₄	2.59
6.5	⁷ / ₈	¹	² ¹ / ₁₆	⁷ / ₈	¹ ¹³ / ₃₂	³ ⁹ / ₃₂	² ⁹ / ₃₂	⁵ ²¹ / ₃₂	⁵ ¹ / ₈	⁴ ¹ / ₃₂	⁷ / ₈	3.9
8.5	¹	¹ ¹ / ₈	² ⁵ / ₁₆	³¹ / ₃₂	¹ ¹¹ / ₁₆	³ ³ / ₄	² ¹¹ / ₁₆	⁶ ¹⁵ / ₃₂	⁵ ²⁹ / ₃₂	⁴ ²¹ / ₃₂	³¹ / ₃₂	5.69
9.5	¹ ¹ / ₈	¹ ¹ / ₄	² ¹⁹ / ₃₂	¹ ³ / ₃₂	¹ ²⁷ / ₃₂	⁴ ¹ / ₄	² ¹⁵ / ₁₆	⁷ ⁹ / ₃₂	⁶ ¹⁷ / ₃₂	⁵ ⁵ / ₃₂	¹ ¹ / ₁₆	8.06
12	¹ ¹ / ₄	¹ ³ / ₈	² ²⁷ / ₃₂	¹ ¹ / ₄	²	⁴ ¹⁷ / ₃₂	³ ⁹ / ₃₂	⁷ ²⁹ / ₃₂	⁷	⁵ ²⁵ / ₃₂	¹ ³ / ₁₆	10.81
13.5	¹ ³ / ₈	¹ ¹ / ₂	³ ⁵ / ₃₂	¹ ³ / ₈	² ¹ / ₄	⁵ ¹ / ₄	³ ⁵ / ₈	⁸ ¹⁵ / ₁₆	⁷ ³ / ₄	⁶ ³ / ₈	¹ ⁵ / ₁₆	14.42
17	¹ ¹ / ₂	¹ ⁵ / ₈	³ ¹⁵ / ₃₂	¹ ¹ / ₂	² ³ / ₈	⁵ ³ / ₄	³ ²⁹ / ₃₂	⁹ ¹³ / ₁₆	⁷ ¹⁵ / ₁₆	⁶ ⁷ / ₈	³ / ₄	18.06
25	¹ ³ / ₄	²	⁴ ¹ / ₁₆	¹ ²⁵ / ₃₂	² ²⁹ / ₃₂	⁷	⁴ ³¹ / ₃₂	¹¹ ¹³ / ₁₆	⁹ ¹³ / ₁₆	⁸ ¹ / ₂	²⁹ / ₃₂	31.34
35	²	² ¹ / ₄	⁴ ³ / ₈	¹ ³¹ / ₃₂	³ ⁹ / ₃₂	⁷ ³ / ₄	⁵ ⁷ / ₁₆	¹³ ¹ / ₃₂	¹⁰ ¹⁹ / ₃₂	⁹ ³ / ₈	¹ ¹ / ₃₂	43.77
42.5	² ¹ / ₄	² ⁹ / ₁₆	⁵ ¹ / ₈	² ¹ / ₄	³ ³ / ₄	⁸ ³ / ₄	⁶ ⁵ / ₁₆	¹⁴ ²⁷ / ₃₂	¹¹ ²⁷ / ₃₂	¹⁰ ²³ / ₃₂	¹ ⁵ / ₁₆	62.46
55	² ¹ / ₂	² ³ / ₄	⁵ ²³ / ₃₂	² ⁹ / ₁₆	⁴ ¹ / ₈	¹⁰ ¹ / ₄	⁷ ³ / ₃₂	¹⁷ ¹ / ₁₆	¹³	¹² ⁷ / ₃₂	¹ ¹ / ₄	87.27
85	³	³ ¹ / ₄	⁶ ³ / ₈	² ⁷ / ₈	⁵	¹² ¹⁵ / ₁₆	⁷ ¹⁵ / ₃₂	²⁰ ³ / ₄	¹⁴ ³¹ / ₃₂	¹³ ³ / ₈	¹ ¹⁷ / ₃₂	136.69

CAD RFID



* For shackles ≥ WLL 2 t